

Dräger Oxygen Booster DOB-H Oxygen Booster Pump

Small, sturdy and effective: the mobile Dräger Oxygen Booster DOB-H, a single-stage, dual-action piston pump, is indispensable in all situations where high-pressure oxygen is needed in apparatus cylinders but no power source is available.



Benefits

Flexible and mobile

The mobile Dräger Oxygen Booster (DOB-H) is operated manually and is characterized by its flexible applications:

- for firefighting
- for mining
- for recreational diving
- at humanitarian and emergency organizations, Red Cross, Technical Emergency Corps, etc.
- for military applications

Efficient, cost-effective and ready for use

With a total weight of only 50 kg, the Dräger DOB-H is equipped with a logistical fill panel, incl. valves, extension hose, pressure gauge and a robust pump block made of heat-absorbing brass. The oxygen is pumped manually from the storage cylinders into the apparatus cylinder to be filled. Several cylinders can be connected at the same time using a connection adapter which is an available option. Due to its design, the Dräger DOB-H is even ready for use at locations without a power supply or in the event of emergencies.

Excellent design

Contamination by lubricants is ruled out due to alternative piping not being required. Wear and tear as well as maintenance tasks are reduced to a minimum because of the high-quality components and elements. Optionally, the pump is also available as a wall mounted version (Dräger DOB-HW). Tool and spare part kits are supplied with the pump. Customer-specific connections are also available on request.

Tested safety

All Dräger oxygen booster pumps are manufactured to ISO 9001 as well as being approved and certified by TÜV and BAM.

Related Products



Dräger Oxygen Booster DOB 200/300

The stationary Dräger Oxygen Booster DOB 200 and Dräger Oxygen Booster DOB 300 allow oxygen at pressures of up to 300 bar to be efficiently decanted from storage cylinders into apparatus cylinders.

Technical Data

Dräger Oxygen Booster DOB-H

Nominal pressure (bar)	200 + 10 %	
Max. operating pressure (bar)	220 positive pressure	
Drive	Manually operated	
Pump	Dry run double plunger compressor	
Filling connection	Standard connection acc. to DIN 477 G 3/4 for oxygen	
Weight (kg)	approx. 50	
Dimensions of container (L x W x H in mm)	DOB-HT 200	approx. 860 x 560 x 330
	DOB-HG 200	approx. 655 x 435 x 270

Ordering Information

Dräger Oxygen Booster DOB-H

65 31 000
65 31 300
65 30 600
65 31 719
65 31 720
65 31 721
65 31 049
65 31 046
65 31 063

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

REGION EUROPE CENTRAL AND EUROPE NORTH

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION EUROPE SOUTH

Dräger Safety France SAS 25, rue Georges Besse 92182 Antony Cedex Tel +33 1 46 11 56 00 Fax +33 1 40 96 97 20 europe.south@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Safety Asia Pte Ltd 25 International Business Park #04-20/21 German Centre Singapore 609916 Tel +65 6308 9400 Fax +65 6308 9401 asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L. Complejo Business Park, V tower, 10th floor Panama City Tel +507 377 9100 Fax +507 377 9130 contactcsa@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

